KEL 24 - ECable entry frames



Туре	Order No.	Inserts KT small large	PU		Description
KEL 24 15-E	42209	15 -	4	95.8 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
KEL 24 12-E	42208	11 1	1	Ø5.8 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
KEL 24 9-E	42207	7 2		95.8 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
				730	

Product description

The KEL 24-E offers a larger frame size for routing a greater amount of cables, pipes or conduits.

The cable entry frames KEL24-E series are KEL frames extended with an additional middle frame for routing additional cables. Thus allowing the quick, easy and cost effective routing solution for up to 60 cables.

Advantages

- Warranty of pre-terminated cables remains
- Retrofitting and maintenance can be carried out easily and quickly
- High packing density
- Strain relief according DIN EN 50262

Specification

Material Polyamide

Flame class UL-94 Vo, self-extinguishing
Protection class IP 54, with gasket and correct

selection of the cable inserts

Temperature - 40°C to + 140°C (static)
Properties halogen-free, silicone-free
Cut-out dimensions 62 x 112 mm / page 106

Accessories

KT Cable inserts Page 20 | 22 KEL-EMC Cable collector Page 82 | 84