

KEL 24 - MT

Cable entry frames



Description	Type	Order No.	Inserts KT small large	PU
-------------	------	-----------	-----------------------------	----

1

Product description

The KEL24-MT provides additional cable routing possibilities - route up to 80 cables.

The cable entry frames KEL24-MT series are KEL frames extended with an additional middle frame for routing additional cables. Thus allowing the quick, easy and cost effective routing solution for up to 80 cables.

Advantages


- Warranty of pre-terminated cables remains
- Retrofitting and maintenance can be carried out easily and quickly
- High packing density
- Strain relief according DIN EN 50262

Specification

Material	Polyamide
Flame class	UL-94 Vo, self-extinguishing
Protection class	IP 54, with gasket and correct selection of the cable inserts
Temperature	-40°C to + 140°C (static)
Properties	halogen-free, silicone-free
Cut-out dimensions	82 x 112 mm / page 124 125
Height KEL	17 mm

Accessories

KT Cable inserts	Page 24 28
KEL-EMC Cable collector	Page 92 94



KEL
24 | 20-MT

Order No.


42232

Inserts KT
small | large

20 | -

PU

1



KEL
24 | 17-MT


Order No.

42224

Inserts KT
small | large

16 | 1

1



KEL
24 | 14-MT


Order No.

42225

Inserts KT
small | large

12 | 2

1



KEL
24 | 8-MT

Order No.

42221

Inserts KT
small | large

4 | 4

1

KEL 24 - 2MT

Cable entry frames



Type	Order No.	Inserts KT small large	PU	Description
------	-----------	-----------------------------	----	-------------

KEL 24 30-2 MT	42234	30 -	1	
KEL 24 27-2 MT	42233	26 1	1	
KEL 24 24-2 MT	42227	22 2	1	
KEL 24 21-2 MT	42226	18 3	1	
KEL 24 12-2 MT	42223	6 6	1	

Product description

The KEL24-2MT is our largest frame offering with the ability to route up to 120 cables.

The cable entry frames KEL24-2MT series are KEL frames extended with two additional middle frames for routing additional cables. Thus allowing the quick, easy and cost effective routing solution for up to 120 cables.

Advantages

- Warranty of pre-terminated cables remains
- Retrofitting and maintenance can be carried out easily and quickly
- High packing density
- Strain relief according to DIN EN 50262

Specification

Material	Polyamide
Flame class	UL-94 Vo, self-extinguishing
Protection class	IP 54, with gasket and correct selection of the cable inserts
Temperature	-40°C to +140°C (static)
Properties	halogen-free, silicone-free
Cut-out dimensions	126 x 112 mm / page 124 125
Height KEL	17 mm

Accessories

KT Cable inserts	Page 24 28
KEL-EMC Cable collector	Page 92 94