KEL - FG Flange enclosure



Order No.

Inserts KT

small | large

10 | -

6|1

2 | 2

PU

1

1

Product description

The cable entry frames range KEL-FG are suited for installation, sealing and strain relief of pre-terminated cables and conduits at an angle of 90° to the cabinet.

For routing cables and conduits up to 34 mm diameter.

Advantages

- Installation at an angle of 90° to the cabinet
- Mechanical protection of cable directly at the place of entry

ABS

- Protection against water spray and drips
- Warranty of pre-terminated cables remains
- Strain relief according DIN EN 50262

Specification

Material Flame class Protection class

Temperature Properties


UL-94 Vo, self-extinguishing IP 54, with gasket and correct selection of the cable inserts - 40°C to + 140°C (static) halogen-free, silicone-free 36 x 112 mm, page 124 | 125

Accessories

Cut-out dimensions

KT Cable inserts **KEL-SNAP SNAP frames** KEL-EMC Cable collector

Page 24 | 28 Page 17 Page 92 | 94



0

0

Description

KEL-FG 42324 Α4

KEL - FG Flange enclosure



The cable entry frames range KEL-FG are suited for installation, sealing and strain relief of pre-terminated cables and conduits at an angle of 90° to the cabinet.

For routing cables and conduits up to 34 mm diameter.

Advantages

- Installation at an angle of 90° to the cabinet Mechanical protection of cable directly at the place of entry
- Protection against water spray and drips
- Warranty of pre-terminated cables remains
- Strain relief according DIN EN 50262

Specification

Material Flame class Protection class

Temperature

Properties Cut-out dimensions

ABS UL-94 Vo, self-extinguishing IP 54, with gasket and correct selection of the cable inserts - 40°C to + 140°C (static) halogen-free, silicone-free 46 x 36 mm, page 124 | 125

Accessories

KT Cable inserts	Page 24 28
KEL-SNAP SNAP frames	Page 17
KEL-EMC Cable collector	Page 92 94

15

