

# KEL - QUICK

## Cable entry frames



1

### Product description

The KEL-QUICK range is a compact system to route and seal assembled cables.

After populating the entry frame with inserts and cables, the two halves of the cable entry frame are SNAPPED together without using tools.

Inserts of the QT range are used.

### Advantages

- Quick and safe assembly without using any tools or screws
- Warranty of pre-terminated cables remains
- Retrofitting and maintenance can be carried out easily and quickly
- High packing density, wide variety of frames and inserts

### Specification

|                   |   |
|-------------------|---|
| Material          | Polyamide   |
| Flame class       | UL-94 Vo, self-extinguishing                                  |
| Protection class  | IP 54, with gasket and correct selection of the cable inserts |
| Temperature       | - 40°C to + 140°C (static)                                    |
| Properties        | halogen-free, silicone-free                                   |
| Drilling template | see page 124   125  |

### Accessories

|                          |              |
|--------------------------|--------------|
| QT Cable inserts         | Page 43      |
| KEL-SNAP SNAP frames     | Page 17      |
| KEL- EMC Cable collector | Page 92   94 |

| Description | Type             | Order No. | Cut-out [mm] | Inserts | PU |
|-------------|------------------|-----------|--------------|---------|----|
|             | KEL-QUICK B4     | 42434     | 46 x 46      | 4 QT    | 10 |
|             | KEL-QUICK B2     | 42430     | 46 x 46      | 2 QT    | 10 |
|             | KEL-QUICK 16   8 | 42418     | 36 x 86      | 8 QT    | 10 |

# KEL - QUICK

## Cable entry frames




### Alternative fastening:

For quick fastening of KEL-QUICK we developed QUICK-PIN. The expansion pins are pressed into the existing bore holes. The flat seal and the KEL-QUICK cable entry frame will be fixed by pressing the threaded pins into the expansion pins.



| Description | Type | Order No. | Cut-out [mm] | Inserts | PU |
|-------------|------|-----------|--------------|---------|----|
|-------------|------|-----------|--------------|---------|----|




KEL-QUICK  
16 | 4

42414

36 x 86

4 QT

10




KEL-QUICK  
24 | 10

42410

36 x 112

10 QT

10



KEL-QUICK  
24 | 5

42415

36 x 112

5 QT

10

Fastening-set

QUICK-PIN

42405

-

-

40

1

## Product description

The KEL-QUICK range is a compact system to route and seal assembled cables.

After populating the entry frame with inserts and cables, the two halves of the cable entry frame are SNAPPED together without using tools.

Inserts of the QT range are used.

## Advantages

- Quick and safe assembly without using any tools or screws
- Warranty of pre-terminated cables remains
- Retrofitting and maintenance can be carried out easily and quickly
- High packing density, wide variety of frames and inserts

## Specification

|                   |   |
|-------------------|---|
| Material          | Polyamide   |
| Flame class       | UL-94 Vo, self-extinguishing                                  |
| Protection class  | IP 54, with gasket and correct selection of the cable inserts |
| Temperature       | - 40°C to + 140°C (static)                                    |
| Properties        | halogen-free, silicone-free                                   |
| Drilling template | see page 124   125  |

## Accessories

|                          |              |
|--------------------------|--------------|
| QT Cable inserts         | Page 43      |
| KEL-SNAP SNAP frames     | Page 17      |
| KEL- EMC Cable collector | Page 92   94 |